



**Single Door**

(width)		Primed In-swing	Primed Out-swing	Clad In-swing	Clad Out-swing	*Tecton In-swing
2-0	RO	26-1/2"	26-1/2"	26"	26"	---
	UD	25-1/2"	25-1/2"	25-1/2"	25-1/2"	---
	BM	28"	28-1/2"	26-5/8"	26-1/2"	---
2-4	RO	30-1/2"	30-1/2"	30"	30"	---
	UD	29-1/2"	29-1/2"	29-1/2"	29-1/2"	---
	BM	32"	32-1/2"	30-5/8"	30-1/2"	---
2-6	RO	32-1/2"	32-1/2"	32"	32"	---
	UD	31-1/2"	31-1/2"	31-1/2"	31-1/2"	---
	BM	34"	34-1/2"	32-5/8"	32-1/2"	---
2-8	RO	34-1/2"	34-1/2"	34"	34"	34-9/16"
	UD	33-1/2"	33-1/2"	33-1/2"	33-1/2"	33-11/16"
	BM	36"	36-1/2"	34-5/8"	34-1/2"	---
2-10	RO	36-1/2"	36-1/2"	36"	36"	---
	UD	35-1/2"	35-1/2"	35-1/2"	35-1/2"	---
	BM	38"	38-1/2"	36-5/8"	36-1/2"	---
3-0	RO	38-1/2"	38-1/2"	38"	38"	38-9/16"
	UD	37-1/2"	37-1/2"	37-1/2"	37-1/2"	37-11/16"
	BM	40"	40-1/2"	38-5/8"	38-1/2"	---
3-6	RO	44-1/2"	44-1/2"	44"	44"	----
	UD	43-1/2"	43-1/2"	43-1/2"	43-1/2"	----
	BM	46"	46-1/2"	44-5/8"	44-1/2"	----

RO = Rough Opening

UD = Unit Dimension (outside of jamb to outside of jamb measurement).  
UD may vary 1/16" +/-

BM = outside of Brickmould to outside of brickmould measurement. The Clad In-Swing dimension is calculated using the Crownline brickmould profile. For Classic brickmould, add 2-9/16" to the Clad In-swing UD.

BM may vary 1/16" +/-

**Single Door w/ Single 12" Sidelite (width)**

2-8	RO	47-15/16"	47-15/16"	47-9/16"	48-3/4"	47-9/16"
	UD	47"	47"	47"	48-1/4"	46-15/16"
	BM	49-1/2"	49-3/4"	48-1/8"	49-3/8"	---
3-0	RO	51-15/16"	51-15/16"	51-9/16"	52-3/4"	51-9/16"
	UD	51"	51"	51"	52-1/4"	50-15/16"
	BM	53-1/2"	53-3/4"	52-1/8"	53-3/8"	---

**Spread Mulls**  
To calculate RO when using a spread mull, add the width of the spread mull(s) to the appropriate rough opening.

**Single Door w/ Double 12" Sidelite (width)**

2-8	RO	61-7/16"	61-7/16"	61-1/16"	63-5/8"	61-1/16"
	UD	60-1/2"	60-1/2"	60-1/2"	63"	60-7/16"
	BM	63"	63-1/4"	61-5/8"	64-1/8"	---
3-0	RO	65-7/16"	65-7/16"	65-1/16"	67-5/8"	65-1/16"
	UD	64-1/2"	64-1/2"	64-1/2"	67"	64-7/16"
	BM	67"	67-1/4"	65-5/8"	68-1/8"	---

\*Cannot use Handicap sills with Tecton Frames

**Single Door w/ Single 14" Sidelite (width)**

2-8	RO	49-15/16"	49-15/16"	49-9/16"	50-3/4"	49-9/16"
	UD	49"	49"	49"	50-1/4"	48-15/16"
	BM	51-1/2"	51-3/4"	50-1/8"	51-3/8"	---
3-0	RO	53-15/16"	53-15/16"	53-9/16"	54-3/4"	53-9/16"
	UD	53"	53"	53"	54-1/4"	52-15/16"
	BM	55-1/2"	55-3/4"	54-1/8"	55-3/8"	---

**Single Door w/ Double 14" Sidelite (width)**

2-8	RO	65-7/16"	65-7/16"	65-1/16"	67-5/8"	65-1/16"
	UD	64-1/2"	64-1/2"	64-1/2"	67"	64-7/16"
	BM	67"	67-1/4"	65-5/8"	68-1/8"	---
3-0	RO	69-7/16"	69-7/16"	69-1/16"	71-5/8"	69-1/16"
	UD	68-1/2"	68-1/2"	68-1/2"	71"	68-7/16"
	BM	71"	71-1/4"	69-5/8"	72-1/8"	---



		Primed & In-swing	Primed & Out-swing	Clad In-swing	Clad Out-swing
2-6 w/2-6 (5-0 unit)	RO	63-7/8"	63-7/8"	63-1/2"	64-3/4"
	UD	62-7/8"	62-7/8"	62-7/8"	64-1/8"
	BM	65-3/8"	65-3/8"	64"	65-1/4"
2-8 w/ 2-8 (5-4 unit)	RO	67-7/8"	67-7/8"	67-1/2"	68-3/4"
	UD	66-7/8"	66-7/8"	66-7/8"	68-1/8"
	BM	69-3/8"	69-3/8"	68"	69-1/4"
3-0 w/3-0 (6-0 unit)	RO	75-7/8"	75-7/8"	75-1/2"	76-3/4"
	UD	74-7/8"	74-7/8"	74-7/8"	76-1/8"
	BM	77-3/8"	77-3/8"	76"	77-1/4"

RO = Rough Opening

UD = Unit Dimension  
(outside of jamb to  
outside of jamb  
measurement).  
UD may vary 1/16" +/-

BM = outside of brickmould to  
outside of brickmould  
measurement. The Clad  
In-Swing dimension is  
calculated using the  
Crownline brickmould  
profile. For Classic  
brickmould, add 2-9/16"  
to the Clad In-swing UD.

BM may vary 1/16" +/-

5-0	RO	62-7/8"	62-7/8"	62-1/2"	62-1/2"
	UD	62"	62"	62"	62"
	BM	64-3/4"	65"	63-3/16"	63"
5-4	RO	66-7/8"	66-7/8"	66-1/2"	66-1/2"
	UD	66"	66"	66"	66"
	BM	68-1/2"	69"	67-3/16"	67"
6-0	RO	74-7/8"	74-7/8"	74-1/2"	74-1/2"
	UD	74"	74"	74"	74"
	BM	76-1/2"	77"	75-3/16"	75"

**Primed Jamb**

		Standard Sills	Handicap In-Swing	Handicap Out-Swing	Bumper Out-Swing
6-8	RO	82-1/8"	81-1/4"	81-1/8"	81-3/8"
	UD	81-11/16"	80-3/4"	80-3/4"	80-15/16"
	BM	82-15/16"	82-1/16"	82-1/4"	82-1/2"
7-0	RO	86-1/8"	85-1/4"	85-1/8"	85-3/8"
	UD	85-11/16"	84-3/4"	84-3/4"	84-15/16"
	BM	86-15/16"	86-1/16"	86-1/4"	86-1/2"
8-0	RO	98-1/8"	97-1/4"	97-1/8"	97-3/8"
	UD	97-11/16"	96-3/4"	96-3/4"	96-15/16"
	BM	98-15/16"	98-1/16"	98-1/4"	98-1/2"

BM = bottom of sill to top of  
brickmold measurement.  
The Clad in-swing  
dimension is calculated  
using the Crownline  
brickmold profile. For  
classic brickmold, add  
1 1/4" to the respective  
UD height (inswing only).

BM may vary 1/16" +/-

**Clad Jamb**

		Standard Sills	Handicap In-Swing	Handicap Out-Swing	Bumper Out-Swing
6-8	RO	81-15/16"	81-1/16"	80-15/16"	81-3/16"
	UD	81-11/16"	80-3/4"	80-13/16"	81"
	BM	82-1/4"	81-5/16"	81-3/8"	81-9/16"
7-0	RO	85-15/16"	85-1/16"	84-15/16"	85-3/16"
	UD	85-11/16"	84-3/4"	84-13/16"	85"
	BM	86-1/4"	85-5/16"	85-3/8"	85-9/16"
8-0	RO	97-15/16"	97-1/16"	96-15/16"	97-3/16"
	UD	97-11/16"	96-3/4"	96-13/16"	97"
	BM	98-1/4"	97-5/16"	97-3/8"	97-9/16"

**Transom Heights**

Please refer to rough opening heights listed on Transom pages 2 and 3 of this section.